

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0751-CPR.2-003.0-06

In compliance with Regulation (EU) 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

**Factory made mineral wool (MW) products for thermal insulation of building
equipment and industrial installations**
(details cf. annex)

Placed on the market under the name or trade mark of

SAINT-GOBAIN ISOVER G+H AG

Bürgermeister-Grünzweig-Str. 1
67059 Ludwigshafen
Germany

and produced in the manufacturing plant

Speyer

Industriestraße 125
67346 Speyer
Germany

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14303:2009+A1:2013

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 21.11.2013 and will remain valid (but no longer than 02.12.2026) as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Gräfelfing, 02.12.2025

Certification Body



Ralph Alberti



Factory: Speyer, Industriestraße 125, 67346 Speyer, Germany

Construction product(s): Factory made mineral wool (MW) products for thermal insulation of building equipment and industrial installations according to EN 14303:2009+A1:2013

Intended use: Thermal insulation products for building equipment and industrial installations

Reaction to fire: Products for which a clearly identifiable stage in the production process results in an improvement in the reaction to fire classification by limiting of organic material.

Detailed information on reaction to fire can be found in the classification reports

Product				Reaction to fire		
Name	Form	Lamination	Nominal dens	Fire class	Range	Classification report
Rohling 5 kPa - Stadur	Slab	-	14 kg/m ³	A1	Max. organic content: 6,4 % or 1,4 kg/m ³	KB-Hoch -130032
FT	Roll	-	15 kg/m ³ - 22 kg/m ³	A1	Max. organic content: 6,4 % or 1,4 kg/m ³	KB-Hoch -130032
FE	Roll	-	19 kg/m ³	A1	Max. organic content: 6,4 % or 1,4 kg/m ³	KB-Hoch -130032
Metac UF-035 / si	Roll	-	19 kg/m ³	A1	Max. organic content: 6,4 % or 1,4 kg/m ³	KB-Hoch -130032

Name	Form	Lamination	Nominal dens	Fire class	Range	Classification report
Rohling 10 kPa - Stadur	Slab	-	19 kg/m ³	A1	Max. organic content: 6,4 % or 1,4 kg/m ³	KB-Hoch -130032
P4	Slab	-	23 kg/m ³	A1	Max. organic content: 6,4 % or 1,4 kg/m ³	KB-Hoch -130032
FK	Roll	-	24 kg/m ³	A1	Max. organic content: 6,4 % or 1,4 kg/m ³	KB-Hoch -130032
TECH ROLL 2.0	Roll	-	24 kg/m ³	A1	Max. organic content: 6,4 % or 1,4 kg/m ³	KB-Hoch -130032
FK/AGF	Roll	Reinforced aluminum foil	24 kg/m ³	A1	Max. organic content: 4,8 %	KB-Hoch-141181
TECH ROLL 2.0 Alu1	Roll	Reinforced aluminum foil	24 kg/m ³	A1	Max. organic content: 4,8 %	KB-Hoch-141181
FK/G-H	Roll	Side glass tissue	24 kg/m ³	A1	Max organic content: 5,4 % or 1,6 kg/m ³	KB-Hoch-190098
TECH ROLL 2.0 V1	Roll	Side glass tissue	24 kg/m ³	A1	Max organic content: 5,4 % or 1,6 kg/m ³	KB-Hoch-190098

Name	Form	Lamination	Nominal densi	Fire class	Range	Classification report
CLIMCOVER Lamella Mat	Lamella mat	Reinforced aluminum foil	27 kg/m ³	A1	Max. organic content: 4,8 %	KB-Hoch-141181
ML 3	Lamella mat	Reinforced aluminum foil	27 kg/m ³	A1	Max. organic content: 4,8 %	KB-Hoch-141181
PF 28	Slab	-	28-36 kg/m ³	A1	Max. Organic content: 5,4 % or 2,8 kg/m ³	KB-Hoch-170365
FI	Roll	-	30 kg/m ³	A1	Max. Organic content: 5,4 % or 2,8 kg/m ³	KB-Hoch-170365
P 4/V	Slab	Side glass tissue	38 kg/m ³	A1	Max organic content: 5,4 % or 1,6 kg/m ³	KB-Hoch-190098
PF 45	Slab	-	45 kg/m ³	A1	Max. Organic content: 5,4 % or 2,8 kg/m ³	KB-Hoch-170365
PF/V 45	Slab	Side glass tissue	45 kg/m ³	A1	Max organic content: 5,4 % or 1,6 kg/m ³	KB-Hoch-190098
ML-DT	Lamella mat	Reinforced aluminum foil	48 kg/m ³	A1	Max. Organic content: 5,4 % or 2,8 kg/m ³	KB-Hoch-170365

Name	Form	Lamination	Nominal dens	Fire class	Range	Classification report
Tech Lamella Mat 2.0	Lamella mat	Reinforced aluminum foil	48 kg/m ³	A1	Max. Organic content: 5,4 % or 2,8 kg/m ³	KB-Hoch-170365
PF 55	Slab	-	55 kg/mm3	A1	Max. Organic content: 5,4 % or 2,8 kg/m ³	KB-Hoch-170365

Gräfeifing: 02.12.2025

Certification body



Ralph Alberti

Ralph Alberti