

# CERTIFICATE OF CONSTANCY OF PERFORMANCE

**0751-CPR.2-003.0-06**

In compliance with Regulation (EU) 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

**Factory made mineral wool (MW) products for thermal insulation of building equipment and industrial installations**  
(details cf. annex)

Placed on the market under the name or trade mark of

**SAINT-GOBAIN ISOVER G+H AG**

Bürgermeister-Grünzweig-Str.1  
67059 Ludwigshafen  
Germany

and produced in the manufacturing plant

**Speyer**

Industriestraße 125  
67346 Speyer  
Germany

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

**EN 14303:2009+A1:2013**

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

**constancy of performance of the construction product.**

This certificate was first issued on 17.02.2014 and will remain valid (but no longer than 02.12.2021) as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Gräfelfing, 02.12.2020



Certification Body

*Ralph Alberti*

Dipl.-Ing. Ralph Alberti

Factory: Speyer, Industriestraße 125, 67346 Speyer, Germany

Construction product(s): Factory made mineral wool (MW) products for thermal insulation of building equipment and industrial installations according to EN 14303:2009+A1:2013

Intended use: Thermal insulation products for building equipment and industrial installations

Level(s) or class(es) reaction to fire: for uses subject to regulations on reaction to fire A1/A2. Products for which a clearly identifiable stage in the production process results in an improvement in the reaction to fire classification by limiting of organic material.

Attestation of conformity system: 1

No.	Form	Name	Product Description	Nominal density	Reaction to fire EN 13501-1			
					Classi- fication	Range	Fire Group	Classification report
1	Roll	<b>FT/AGF</b>	Roll made of non-combustible mineral wool covered with reinforced aluminum foil	14 kg/m <sup>3</sup> - 22 kg/m <sup>3</sup>	A1	Organic content: 4,8 %	6	KB-Hoch-141181
2	Roll	<b>FT</b>	Roll made of non-combustible mineral wool	15 kg/m <sup>3</sup> - 22 kg/m <sup>3</sup>	A1	Organic content: 6,4 %	3	KB-Hoch -130032
3	Roll	<b>FE</b>	Roll made of non-combustible mineral wool	19 kg/m <sup>3</sup>	A1	Organic content: 6,4 %	3	KB-Hoch -130032
4	Roll	<b>FE/AGF</b>	Roll made of non-combustible mineral wool covered with reinforced aluminum foil	19 kg/m <sup>3</sup>	A1	Organic content: 4,8 %	6	KB-Hoch-141181
5	Slab	<b>P4/GW</b>	Slab made of non-combustible mineral wool	23 kg/m <sup>3</sup>	A1	Organic content: 6,4 %	3	KB-Hoch -130032
6	Roll	<b>FK</b>	Roll made of non-combustible mineral wool	24 kg/m <sup>3</sup>	A1	Organic content: 6,4 %	3	KB-Hoch -130032
7	Roll	<b>FK/AGF</b>	Roll made of non-combustible mineral wool covered with reinforced aluminum foil	24 kg/m <sup>3</sup>	A1	Organic content: 6,4 %	3	KB-Hoch -130032





No.	Form	Name	Product Description	Reaction to fire EN 13501-1				
				Nominal density	Classification	Range	Fire Group	Classification report
8	Roll	<b>FK/G-H</b>	Roll made of non-combustible mineral wool covered with reinforced aluminum foil	24 kg/m <sup>3</sup>	A1	Organic content: 4,8 %	6	KB-Hoch-141181
9	Slab	<b>PF 28</b>	Slab made of non-combustible mineral wool	28 kg/m <sup>3</sup>	A1	-	4	230008616/6
10	Roll	<b>FI</b>	Roll made of non-combustible mineral wool	30 kg/m <sup>3</sup>	A1	-	4	230008616/6
11	Lamella mat	<b>ISOVER Lamellenmatten ML 3</b>	Lamella mat made of non-combustible mineral wool covered with rein-forced aluminium foil	27 kg/m <sup>3</sup>	A1	Organic content: 4,8 %	6	KB-Hoch-141181
		<b>CLIMCOVER Lamella Mat</b>						
12	Lamella mat	<b>ISOVER Druckfeste Lamellenmatten ML-DT</b> <b>Tech Lamella Mat 2.0</b>	Lamella mat made of non-combustible mineral wool covered with rein-forced aluminum foil	48 kg/m <sup>3</sup>	A1	Organic content: 5,4 %	10	KB-Hoch-170365

Detail information about the insulation products are given in the classification reports

Gräfelfing 02.12.2020



Certification Body

*Ralph Alberti*

Dipl.-Ing. Ralph Alberti